

# INVERTER MINI SPLIT



- Inverter Technology
- High Efficiency
- 3D Air Flow
- Auto-Restart Function
- Silent Operation
- Fast Cooling Mode
- Self-Clean Mode
- Easy to Install
- Hidden LED Display
- Wireless Remote Control
- Built for long-term reliability

BTU's  
9,000  
12,000  
18,000  
24,000

MODEL		EV13C1A3	EV13C2A3	EV18C2A3	EV24C2A3	EV36H2A3	
SYSTEM	CAPACITY	BTU/H	12,000	12,000	18,000	24,000	36,000
	EFFICIENCY	SEER	17	17	16	17	17
	ELECTRICAL	Volt / Hertz	115V / 60Hz	208~230V / 60Hz	208~230V / 60Hz	208~230V / 60Hz	208~230V / 60Hz
		Rated Current (A)	14	5.8	8.9	11.4	16.5
	OPER. AMBIENT TEMPERATURE	°F (°C)	63 ~ 90 (17 ~ 32)				
	AREA OF APPLICATION	(Ft²)	500	500	750	900	1250
	MOSITURE REMOVAL	Liter/Hr	1.2	1.2	1.8	2.4	3
	REFRIGERANT	R410A (g)	820	820	1100	1420	2500
		Liquid (in)	1/4"	1/4"	1/4"	1/4"	3/8"
	REFRIGERATION CONNECTION	Suction (in)	1/2"	1/2"	1/2"	5/8"	5/8"
Maximum Length (Ft)		82	82	98	98	190	
Maximum Height (Ft)		33	33	66	66	66	
INTERIOR UNIT	AIR FLOW	CFM	170 ~ 285	190 ~ 305	295 ~ 395	330 ~ 585	470 ~ 795
	SOUND LEVEL	dB(A)	25 ~ 37	25 ~ 39	33 ~ 45	36 ~ 47	44 ~ 52
	CONTROL	Control Type	LCD REMOTE CONTROL				
		Auto Restart	YES				
	DIMENSIONS	Unit W x H x D (in)	33 1/2 x 11 3/4 x 7 3/4	29 1/2 x 11 1/4 x 8	35 1/2 x 12 1/4 x 8 3/4	45 1/2 x 13 x 8 3/4	49 1/4 x 14 1/4 x 10
	WEIGHT	Unit (LBS.)	23	18	29	30	40
EXTERIOR UNIT	COMPRESSOR	RLA	6.1	5.8	7.3	8	5.1
	SOUND LEVEL	dB(A)	53	52	57	57	62
	DIMENSIONS	Unit W x H x D (in)	28 1/4 x 21 1/4 x 10 1/4	28 1/4 x 21 1/4 x 10 1/4	31 1/2 x 21 x 11 3/4	32 1/2 x 25 3/4 x 12 1/4	35 1/2 x 27 1/2 x 13 3/4
	WEIGHT	Unit (LBS.)	60	56	71	89	113

\*Specifications are subject to changes without notice. \*\* Model numbers, pictures, and specifications of all products are subject to change without further notice.

Distributed by:

### ACCESSORIES INCLUDED



- 3 Meter kit
- Interconnecting cables
- Installation manual
- Plastic protection cover for valves
- LCD Remote Control